

Cooling unit LWH 67

Technical data

A LWH is a compressor chiller that produces cooling water for a wide range of industrial applications. Each unit is equipped with a heat exchanger, an atmospheric open water tank and a corresponding pump.

The waste heat generated during the cooling process is discharged to the ambient air.

The case is self-supporting and coated according to the specification.

Outdoor installation with winter start-up device or other options can be ordered as accessories.

Technical data

Refrigerant	R 410a
Cooling capacity at 32 °C ambient temperature with a water flow of	59,9 67,1 kW +15 +20 °C
Switch hysteresis	+/- 1 K
Ambient temperature	+10 bis +42 °C
Water set point	+ 13,5 bis + 35 °C
Pump power	10,3 m ³ /h
Pump prepressure	3,2 bar
Air performance	15.500 m ³ /h
Maximum ambient temperature	42 °C
Maximum power connection	27,3 kW
Maximum power consumption	46,8 A
Power type	400 V, 50 Hz, 3Ph, PE
Water connections	1 1/2"
Tank capacity	330 l
Weight	420 kg
Dimensions L x B x H	1.000 x 1.000 x 2.000 mm
Sound pressure level at a distance of 1m	71 dB(A)



Image similar

Cooling unit LWH 67

Technical data

Covering

- Powder coated RAL7021
- removable on two sides
- Air inlet from the right
- Hot air outlet upwards

Refrigeration circuit

- Completely hermetic, with all necessary fittings such as service ports, connections for external high and low pressure gauges.
- energy-saving scroll refrigeration compressor
- Stainless steel evaporator in water tank
- Air-cooled condenser with power-controlled fan
- thermostatic expansion valve, receiver, filter drier, high and low pressure switch, sight glass with humidity indicator.
- Suction gas line insulated diffusion-tight
- Oil and refrigerant service charge

Water circuit

- Water tank made of PE, removable tank lid
- Pressure gauge in water supply, tank drain
- Cold water pump, dry running protection for the pump
- optical fill level indicator
- adjustable overflow valve
- Internally completely piped
- External water connections with anti-rotation device

Electrical control panel

- in completely enclosed, dust-tight design
- completely wired with all switching, control and monitoring devices
- Safety chain with high and low pressure switches and motor protection switches
- Adjustable electronic digital thermostat for complete electrical control
- Collective fault signal, potential free
- Remote On/Off
- Power controlled condensing fan

Accessories for cooling unit type LWH:

- | | |
|----------------------------------|---|
| 1. water cooled condenser | 7. hot gas bypass control for increased temperature constancy (+/-0.1K) |
| 2. 2x forward / return flow | 8. insulation of all water-carrying parts |
| 3. Flow monitors | 9. 4,5 kW Heater rod incl. control unit |
| 4. signal message water shortage | 10. winter start direction for fan |
| 5. mobile version | 11. free outdoor installation with winter start device sheets VA and insulation |
| 6. control voltage in 24V DC | |